

# MACINA LYCAN

272 11 PT-CX5I

1x11

SHIMANO  
XT

125mm

16 17 19 21  
41 43 48 53  
cm

BIKE CATEGORY  
**E3**



TAPERED  
STEERER



GRAVITY  
CASTING



INTERNAL  
CABLE ROUTING



HYDRO  
FORM

**MOTOR** BOSCH DRIVE UNIT 36V-250W, 25km/h  
PERFORMANCELINE CX  
**BATTERY** Powertube 13.4Ah - 500Wh  
**DISPLAY** Intuvia LCD Display, Remote w/Walkassist  
**ITEM NO.** 798411xxx  
**COLOUR** Black matt (blue+orange)

**FRAME** Macina Lycan 27.5", Alloy  
4-linkage POP System - 125mm, boost 148mm  
Battery full-Integrated  
**SHOCK** Fox A Float DPS, Perf.  
**FORK** Fox 34 A Float, Perf. GripRem.-T-15x110  
**BRAKE** Shimano Zee M640B 4-piston/ Rotor 203-180  
**SHIFTLEVER** Shimano Deore XT M8000-11

**R. DERAILLEUR** Shimano Deore XT M8000 GS shadow +  
**SPROCKET** Shimano M7000-11-11-46  
**WHEELSET** DT H1900 Hybrid 27-5" B/B Tubeless  
DT Swiss straightpull - Boost 110/148  
**TIRE** Schwalbe Rock Razor, snakeSkin, Addix - 60-584  
**SEATPOST** KTM Comp. JD-YSP22L adjustable, extern vers. w/Rem  
**WEIGHT** 23.1kg with pedal

## GEOS

	Size in cm / inch	Toptube length	Seat angle	Head angle	Headtube length	Chainstay length	Wheelbase	Stack	Reach	Standover height	BB drop
--	----------------------	-------------------	------------	------------	--------------------	---------------------	-----------	-------	-------	---------------------	---------

**MACINA LYCAN**  
271, 272, 273,  
274, 275

41	16	557	74,5°	68,0°	120	486	1163	625	392	791	35
43	17	567	74,5°	68,0°	120	486	1183	625	412	790	35
48	19	583	74,5°	68,0°	125	486	1203	629	431	811	35
53	21	603	74,5°	68,0°	137	486	1225	640	447	840	35